

CHASE PIPELINE PRODUCTS
TAPECOAT® / ROYSTON® DIVISIONS OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET

Product: Roskote A-51 Plus Mastic

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED BY: CHASE CORPORATION PITTSBURGH
201 ZETA DRIVE
PITTSBURGH, PA 15238

GENERAL INFORMATION: (412) 828-1500

EMERGENCY, CHEMTREC: 800-424-9300, Only in the event of chemical emergencies involving a spill, leak, fire, exposure or any accident involving chemicals. Outside USA: (703) 527-3887

REVISION DATE: January 20, 2010
PREPARED BY: Frederick F. Fischer, Jr.

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>CAS NUMBER</u>	<u>IDENTIFICATION</u>	<u>APP. % BY WGT.</u>
108-88-3	Toluene	30-40
78-93-3	Methyl Ethyl Ketone	< 5
65996-93-2	Coal Tar Pitch*	45-50
8007-42-2	Coal Tar Pitch*	< 5
25036-25-3	Epoxy Resin	< 5
12001-26-2	Mica**	5-10
14807-96-6	Talc**	< 5

* Listed as known Carcinogen
** Respiratory dust

3. HAZARDOUS IDENTIFICATION

HAZARDOUS POLYMERIZATION: Will Not Occur

ROUTES OF EXPOSURE: Inhalation, Skin, Eyes and Ingestion.

IMMEDIATE EFFECTS:

INHALATION: Causes irritation of nasal passages and throat. Causes stupor (central nervous system depression).

SKIN CONTACT: Can cause moderate skin injury (reddening and swelling).

EYE CONTACT: Liquid and vapors are irritating to eyes. Can cause severe injury.

INGESTION: Can cause mental sluggishness.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

ACCUTE: Can Cause severe eye irritation, redness, tearing, and blurred vision. Excessive inhalation of vapors can cause nausea, respiratory irritation, central nervous system affects, including dizziness, weakness, fatigue, nausea, headache, and possible unconsciousness and even death. Swallowing can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into lungs can cause chemical pneumonitis, which is fatal.

CHASE PIPELINE PRODUCTS
TAPECOAT[®] / ROYSTON[®] DIVISIONS OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET

CHRONIC: Prolonged and repeated skin contact can cause moderate irritation, defatting and dermatitis. Overexposure in laboratory animals has been found the cause of the following affects: Liver abnormalities, kidney damage, lung damage, and spleen damage. Overexposure to this material has been suggested as a cause for liver abnormalities in humans. Prolonged or repeated contact may lead to dermatitis, and with poor hygiene practices, to skin cancer. An Ingredient in this material has been listed as a carcinogen by IARC, NPT, QSHA, and ACGIH.

4. FIRST AID MEASURES

GENERAL ADVICE: Consult Physician immediately.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. Move to an area free from risk of further exposure. Treat symptomatically. Administer oxygen or artificial respiration as needed. **SEEK MEDICAL ATTENTION.**

SKIN CONTACT: Repeated or prolonged contact can cause drying of skin and dermatitis. Remove contaminated clothing and launder thoroughly before reuse Wash affected skin thoroughly with soap and water. **DO NOT USE SOLVENTS** on skin as they may promote absorption of this material. For severe exposure, get under safety shower after removing clothing, and then **SEEK MEDICAL ATTENTION** if irritation develops or persists after the area has been washed.

EYE CONTACT: Remove contact lenses. Flush eyes with large amounts of water, preferably lukewarm water, for at least 15 minutes. Refer individual to a physician or ophthalmologist for immediate follow up. **SEEK MEDICAL ATTENTION.**

INGESTION: **DO NOT INDUCE VOMITING.** Give 1-2 cups of milk or water to drink. **DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SEEK MEDICAL ATTENTION.**

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Foam, Carbon Dioxide or dry chemical. Use self-contained breathing apparatus if applicable.

EXPLOSION DATA:

SENSITIVITY TO MECHANICAL IMPACT: Stable

SENSITIVITY TO STATIC DISCHARGE: Expected to be sensitive to static discharge when vapors are present between the lower and upper explosive limits.

6. ACCIDENTAL RELEASE MEASURES

PRECAUTIONS FOR PERSONNEL: Wear protective clothing. Use self-contained breathing apparatus if required.

ENVIRONMENTAL PRECAUTIONS: Avoid discharge to drains, sewers and natural water supply.

PROCESS FOR CLEANING: Absorb with inert material. Remove sources of ignition. Scoop material with non-sparking tools.

7. HANDLING AND STORAGE

HANDLING: Ventilate work area sufficiently. Keep containers closed. Avoid contact with eyes, skin and clothing.

CHASE PIPELINE PRODUCTS
TAPECOAT® / ROYSTON® DIVISIONS OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET

STORAGE: Store between -15°C and +35°C for solvent based coatings and thinners. Ground all metal containers. 55-gallon drums may be stored on their sides in a cradle designed for this purpose.

8. EXPOSURE RESTRICTIONS AND PERSONAL PROTECTION

MATERIALS WITH LIMITS THAT REQUIRE SUPERVISION:

<u>CAS NUMBER</u>	<u>IDENTIFICATION</u>	<u>APP. % BY WGT.</u>	<u>NIOSH REL</u>	<u>VALUE</u>	<u>UNIT</u>
08-88-3	Toluene	30-40	TWA	50	ppm
78-93-3	Methyl Ethyl Ketone	< 5	TWA	200/ 590	ppm(mg/m ³)
65996-93-2	Coal Tar Pitch	45 -50	TWA	0.2	mg/m ³
8007-42-2	Coal Tar Pitch	< 5	TWA	0.2	mg/m ³
25036-25-3	Epoxy Resin	< 5	TWA	5.0	mg/m ³
12001-26-2	Mica	5-10	TWA	10.0	mg/m ³
14807-96-6	Talc	< 5	TWA	2.0	mg/m ³

ADDITIONAL ADVICE: Use personal protective equipment, i.e., suitable work clothing, eye goggles and protective gloves. If spraying utilize protective facemask.

9. PHYSICAL PROPERTIES

ODOR: AROMATIC

<u>CHANGE OF STATE</u>	<u>VALUE/AREA</u>	<u>UNIT</u>	<u>METHOD</u>
FREEZING POINT:	N/A	°C	
BOILING POINT:	78-110 (174-232)	°C (°F)	
FLASH POINT:	-3.9 (25)	°C (°F)	TCC
IGNITION TEMPERATURE:			
SPECIFIC GRAVITY:	1.107	H ₂ O = 1	
% VOLATILE BY VOLUME:	44-55	%	
SOLUBILITY IN WATER:	NEGLIGABLE		
PH VALUE:	N/A		
VISCOSITY:		CPS	
FLAMMABLE LIMITS:	LEL 1.8 UEL 11.5		
EVAPORATION RATE:	3.3	BUAC = 1	

10. STABILITY AND REACTIVITY

STABILITY: Stable
CONDITIONS TO AVOID: Sparks and Open Flame.
MATERIALS TO AVOID: Contact with strong oxidizing, acidic or alkaline agents.
DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide and Oxides of Nitrogen.
EYES: Splashes or spray vapors may cause irritation.
SKIN: Substance may be an irritant for sensitive skin.
INHALATION: May cause mild nausea/dizziness in some people when used in confined/unventilated areas. Move patient to fresh air. Give nothing by mouth.

CHASE PIPELINE PRODUCTS
TAPECOAT[®] / ROYSTON[®] DIVISIONS OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET

CONSUMPTION:

If accidentally swallowed may cause discomfort and requires plenty of water or milk to dilute. Do not induce vomiting. Seek medical assistance.

CHASE PIPELINE PRODUCTS
TAPECOAT® / ROYSTON® DIVISIONS OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET

11. TOXICOLOGICAL INFORMATION

<u>CAS NUMBER</u>	<u>IDENTIFICATION</u>	<u>DERMAL LD50</u>	<u>INAHALATION LC50</u>	<u>ORAL LD50</u>
108-88-3	Toluene	12.3 g/kg (Rabbit)	4959 ppm (Rat)	7.0 g/kg (Rat)
78-93-3	Methyl Ethyl Ketone	N/E	23,500 mg/m ³ (Rat)	2,737 mg/kg (Rat)
65996-93-2	Coal Tar Pitch	N/E	17 mg/m ³ (Rat)	6,200 mg/kg (Rat)
8007-42-2	Coal Tar Pitch	N/E	17 mg/m ³ (Rat)	6,200 mg/kg (Rat)
25036-25-3	Epoxy Resin	N/E	N/E	N/E
12001-26-2	Mica	N/E	N/E	N/E
14807-96-6	Talc	N/E	N/E	N/E

<u>CAS NUMBER</u>	<u>IDENTIFICATION</u>	<u>CARCINOGENICITY</u>		<u>TERATOGENICITY</u>	<u>MUTAGENICITY</u>
		<u>ACGIH</u>	<u>IARC</u>		
08-88-3	Toluene	N/E	N/E	Yes	N/E
78-93-3	Methyl Ethyl Ketone	N/E	N/E	N/E	N/E
65996-93-2	Coal Tar Pitch	Yes	Yes	N/E	YES
8007-42-2	Coal Tar Pitch	Yes	Yes	N/E	N/E
25036-25-3	Epoxy Resin	N/E	N/E	N/E	N/E
12001-26-2	Mica	N/E	N/E	N/E	N/E
14807-96-6	Talc	N/E	N/E	N/E	N/E

12. ECOLOGICAL INFORMATION

VOLATILE ORGANIC COMPOUNDS: 420 Grams Per Liter (g/l). 3.51 Pounds Per Gallon (lb/g).

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be made in accordance with Federal, State and Local regulations.

14. TRANSPORT INFORMATION

SHIPPING CLASS: UN1263 PAINT FLAMMABLE LIQUID ; PACKING GROUP II

15. REGULATORY INFORMATION

SARA SECTION 302:

SARA (311,312) HAZARD CLASS:

SARA (313) CHEMICALS: TOLUENE, MEK

CERCLA: Toluene: 1000 LBS.; MEK: 5000 LBS.

CPSC CLASSIFICATION:

HMIS: FLAMMABILITY: 3 REACTIVITY: 0 HEALTH: 2

NFPA: FLAMMABILITY: 3 REACTIVITY: 0 HEALTH: 2

CALIFORNIA PROPOSITION 65:

- A. This product contains a chemical known to the State of CA to cause birth defects or other reproductive harm.
- B. This product contains a chemical known to the State of CA to cause cancer.
- C. This product contains a chemical known to the State of CA to cause cancer and birth defects or other reproductive harm.

CHASE PIPELINE PRODUCTS
TAPECOAT[®] / ROYSTON[®] DIVISIONS OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET

16. OTHER INFORMATION

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND ARE NOT A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED IS MADE. THE STATED RECOMMENDED HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE.

C = Ceiling Limit, NEGL = Negligible, N/A = Not Applicable, N/E = Not Established, PROP. = Proprietary.
